

Appl. No. 09/523,329
Amendment dated November 23, 2004
Reply to Office action of August 24, 2004

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1 (Currently amended). A method of communicating data between a base station having a plurality of antennas and at least one mobile terminal, the method comprising the steps of:

transmitting from the base station, derived versions of a midamble signal to each antenna within the plurality of antennas; and

providing a distinct delay associated with each derived version of the midamble signal and its respective antenna; and

further comprising the step of altering the distinct delay associated with a derived version of the midamble signal and its respective antenna if and when an estimated path profile associated with the specific midamble signal changes from a prior estimated path profile.

2 (Original). The method according to claim 1, wherein each derived version of the midamble signal is the midamble signal itself.

3 (Original). The method according to claim 1, wherein at least one derived version of the midamble is formed by scaling the amplitude of the midamble signal.

4 (Original). The method according to claim 1, wherein at least one derived version of the midamble is formed by shifting the phase of the midamble signal.

Appl. No. 09/523,329
Amendment dated November 23, 2004
Reply to Office action of August 24, 2004

5 (Original). The method according to claim 1, wherein at least one derived version of the midamble is formed by scaling the amplitude and shifting the phase of the midamble signal.

6 (Canceled).

7 (Original). The method according to claim 1 further comprising the step of receiving a base station generated distinct delayed time division duplex signal at a respective mobile terminal and demodulating the distinct delayed time division duplex signal via a joint detector.

8 (Original). The method according to claim 1 further comprising the step of receiving a base station generated distinct delayed time division duplex signal at a respective mobile terminal and demodulating the distinct delayed time division duplex signal via a zero-forcing block linear equalizer.

9 (Original). The method according to claim 1 further comprising the step of receiving a base station generated distinct delayed time division duplex signal at a respective mobile terminal and demodulating the distinct delayed time division duplex signal via a zero-forcing block linear equalizer in association with decision feedback.

10 (Original). The method according to claim 1 further comprising the step of receiving a base station generated distinct delayed time division duplex signal at a respective mobile terminal and demodulating the distinct delayed time division duplex signal via a minimum-mean-square equalizer.

Appl. No. 09/523,329
Amendment dated November 23, 2004
Reply to Office action of August 24, 2004

11 (Original). The method according to claim 1 further comprising the step of receiving a base station generated distinct delayed time division duplex signal at a respective mobile terminal and demodulating the distinct delayed time division duplex signal via a minimum-mean-square equalizer associated with decision feedback.

12 (Original). The method according to claim 1 wherein the derived versions of a midamble signal transmitted to each antenna are associated with a code division multiple access data signal.

13 (Previously presented). A method for communicating data between a base station having a plurality of antennas and at least one mobile terminal, the method comprising the steps of:

receiving at the base station, a time division duplex mode uplink signal from each mobile terminal in communication with the base station and estimating a path profile associated with each received uplink signal;

transmitting from the base station, a time division duplex signal to each antenna within the plurality of antennas; and

providing from the base station a distinct delay associated with each transmitted time division duplex signal and its respective antenna.

14 (Original). The method according to claim 13 further comprising the step of altering the distinct delay associated with a specific time division duplex signal and its respective antenna if and when the estimated path profile associated with the specific time division duplex signal changes from its prior estimated path profile.

Appl. No. 09/523,329
Amendment dated November 23, 2004
Reply to Office action of August 24, 2004

15 (Original). The method according to claim 13 further comprising the step of receiving a distinct delayed time division duplex signal at a respective mobile terminal and demodulating the distinct delayed time division duplex signal via a joint detector.

16 (Original). The method according to claim 13 further comprising the step of receiving a distinct delayed time division duplex signal at a respective mobile terminal and demodulating the distinct delayed time division duplex signal via a zero-forcing block linear equalizer.

17 (Original). The method according to claim 13 further comprising the step of receiving a distinct delayed time division duplex signal at a respective mobile terminal and demodulating the distinct delayed time division duplex signal via a zero-forcing block linear equalizer associated with decision feedback.

18 (Original). The method according to claim 13 further comprising the step of receiving a distinct delayed time division duplex signal at a respective mobile terminal and demodulating the distinct delayed time division duplex signal via a minimum mean-square-error equalizer.

19 (Original). The method according to claim 13 further comprising the step of receiving a distinct delayed time division duplex signal at a respective mobile terminal and demodulating the distinct delayed time division duplex signal via a minimum mean-square-error equalizer associated with decision feedback.

Appl. No. 09/523,329
Amendment dated November 23, 2004
Reply to Office action of August 24, 2004

20 (Original). The method according to claim 13 wherein the step of receiving at the base station, a time division duplex mode uplink signal from each mobile terminal in communication with the base station and estimating a path profile associated with each received uplink signal comprises the step of receiving a time division duplex code division multiple access data signal.

21 (Currently amended). A time division duplex communication system comprising:

a base station having a plurality of spaced apart antennas;
signal distribution means for coupling time division duplex communication signals between the base station and the plurality of spaced apart antennas; and

delay means operatively coupled to the plurality of spaced apart antennas and the signal distribution means for providing a distinct delay in each of the time division duplex communication signals coupled between the base station and the plurality of spaced apart antennas, wherein the delay means is operable to alter the distinct delay associated with a time division duplex communication signal if and when an estimated path profile associated with the specific time division duplex communication signal changes from a prior estimated path profile.

22 (Original). The time division duplex communication system according to claim 21 further comprising at least one mobile terminal having a joint detector for receiving and demodulating a delayed time division duplex communication signal received from the base station.

23 (Original). The time division duplex communication system according to claim 21 further comprising at least one mobile terminal having a zero-forcing block linear equalizer configured to demodulate a delayed time division duplex communication signal received from the base station.

Appl. No. 09/523,329
Amendment dated November 23, 2004
Reply to Office action of August 24, 2004

24 (Original). The time division duplex communication system according to claim 21 further comprising at least one mobile terminal having a zero-forcing block linear equalizer having decision feedback capability and configured to demodulate a delayed time division duplex communication signal received from the base station.

25 (Original). The time division duplex communication system according to claim 21 further comprising at least one mobile terminal having a minimum-mean-square error equalizer configured to demodulate a delayed time division duplex communication signal received from the base station.

26 (Original). The time division duplex communication system according to claim 21 further comprising at least one mobile terminal having a minimum-mean-square error equalizer having decision feedback capability and configured to demodulate a delayed time division duplex communication signal received from the base station.

27 (Original). The time division duplex communication system according to claim 21 wherein each time division duplex communication signal is associated with a code division multiple access data signal.

28 (Currently amended). A data communication system comprising:
a base station having a plurality of spaced apart antennas;
at least one mobile terminal in communication with the base station;
and
means for providing a distinct delay associated with each antenna of the plurality of spaced apart antennas such that a time division duplex communication signal coupled between the base station and the plurality of spaced apart antennas

Appl. No. 09/523,329
Amendment dated November 23, 2004
Reply to Office action of August 24, 2004

can be demodulated within the at least one mobile terminal, wherein the delay means is operable to alter the distinct delay associated with a time division duplex communication signal if and when an estimated path profile associated with the specific time division duplex communication signal changes from a prior estimated path profile.

29 (Original). The data communication system according to claim 28 wherein the at least one mobile terminal comprises a joint detector.

30 (Original). The data communication system according to claim 28 wherein the at least one mobile terminal comprises a zero-forcing block linear equalizer.

31 (Original). The data communication system according to claim 28 wherein the at least one mobile terminal comprises a zero-forcing block linear equalizer having decision feedback capability.

32 (Original). The data communication system according to claim 28 wherein the at least one mobile terminal comprises a minimum-mean-square error equalizer.

33 (Original). The data communication system according to claim 28 wherein the at least one mobile terminal comprises a minimum-mean-square error equalizer having decision feedback capability.

34 (Original). The data communication system according to claim 28 wherein the means for providing a distinct delay is capable of providing a distinct delay associated with each antenna such that a code division multiple access communication signal coupled between the base station and the plurality of spaced apart antennas can be demodulated within the at least one mobile terminal.

Appl. No. 09/523,329
Amendment dated November 23, 2004
Reply to Office action of August 24, 2004

35 (Currently amended). A data communication system comprising:
a base station having a plurality of spaced apart antennas;
means for transmitting from the base station, derived versions of a
midamble signal to each antenna within the plurality of spaced apart antennas;
and
means for providing a distinct delay associated with each derived version
of the midamble signal and its respective antenna within the plurality of spaced
apart antennas, wherein the means for providing is operable to alter the distinct
delay associated with each derived version of the midamble signal and its
respective antenna if and when an estimated path profile associated with the
specific midamble signal changes from a prior estimated path profile.

36 (Original). The data communication system according to claim 35 further
comprising means for scaling a midamble signal to generate a derived version of
the midamble signal.

37 (Original). The data communication system according to claim 35 further
comprising means for phase shifting a midamble signal to generate a derived
version of the midamble signal.

38 (Original). The data communication system according to claim 35 further
comprising means for scaling and phase shifting a midamble signal to generate a
derived version of the midamble signal.

39 (Original). The data communication system according to claim 35 further
comprising at least one mobile terminal configured to receive and demodulate a
time division duplex communication signal from the base station.

Appl. No. 09/523,329
Amendment dated November 23, 2004
Reply to Office action of August 24, 2004

40 (Original). The data communication system according to claim 39 wherein the at least one mobile terminal comprises a joint detector.

41 (Original). The data communication system according to claim 39 wherein the at least one mobile terminal comprises a zero-forcing block linear equalizer.

42 (Original). The data communication system according to claim 39 wherein the at least one mobile terminal comprises a zero-forcing block linear equalizer having decision feedback capability.

43 (Original). The data communication system according to claim 39 wherein the at least one mobile terminal comprises a minimum-mean-square error equalizer.

44 (Original). The data communication system according to claim 39 wherein the at least one mobile terminal comprises a minimum-mean-square error equalizer having decision feedback capability.

45 (Original). The data communication system according to claim 39 wherein the at least one mobile terminal is further configured to receive and demodulate a code division multiple access communication signal from the base station.

Appl. No. 09/523,329
Amendment dated November 23, 2004
Reply to Office action of August 24, 2004

46 (Previously presented). A data communication system comprising:
a base station configured to communicate with at least one mobile terminal, the base station having a plurality of spaced apart antennas and further having:
a data processor;
a data input device in communication with the data processor;
an algorithmic software directing the data processor; and
a data storage unit, wherein discrete signal uplink data associated with at least one mobile terminal in communication with the base station is stored and supplied to the data processor such that the data processor, directed by the algorithmic software, can automatically derive midamble signal parameters using algorithmically defined relationships associated with the discrete signal uplink data such that derived midamble signals communicated between the base unit and each respective antenna will be characterized by at least one distinct signal parameter selected from the group consisting of signal delay, signal phase and signal amplitude.

47 (Original). The data communication system according to claim 46 further comprising at least one mobile terminal.

48 (Original). The data communication system according to claim 47 wherein the at least one mobile terminal comprises a joint detector configured to demodulate a time division duplex signal generated by the base station.

49 (Original). The data communication system according to claim 48 wherein the joint detector comprises a zero-forcing block linear equalizer.

50 (Original). The data communication system according to claim 48 wherein the joint detector comprises a zero-forcing block linear equalizer having decision feedback capability.

Appl. No. 09/523,329
Amendment dated November 23, 2004
Reply to Office action of August 24, 2004

51 (Original). The data communication system according to claim 48 wherein the joint detector comprises a minimum-mean-square error equalizer.

52 (Original). The data communication system according to claim 48 wherein the joint detector comprises a minimum-mean-square error equalizer having decision feedback capability.

53 (Original). The data communication system according to claim 46 wherein the data processor is further directed by the algorithmic software such that it can automatically determine signal path profile parameters using algorithmically defined relationships associated with the discrete signal uplink data such that a signal communicated between the base unit and each antenna will be re-characterized by a new distinct signal characteristic if and when the discrete signal uplink data received by the base unit are sufficiently changed to require that a distinct signal delay change by at least one chip from an existing distinct signal delay.

54 (Currently amended). A time-division duplex (TDD) data communication system in which system users communicate information signals through a base station using TDD communication signals, the base station having an antenna system comprising:

- a plurality of spaced apart antennas;
- signal distribution means for coupling TDD communication signals between the base station and the plurality of spaced apart antennas; and

Appl. No. 09/523,329
Amendment dated November 23, 2004
Reply to Office action of August 24, 2004

variable delay means operatively coupled to the plurality of spaced apart antennas and the signal distribution means for providing derived delays associated with the TDD communication signals and the plurality of spaced apart antennas, wherein the variable delay means comprises:

a data processor;

an algorithmic software directing the data processor; and

a data storage unit, wherein discrete signal uplink data associated with at least one mobile terminal in communication with the base station is stored and supplied to the data processor such that the data processor, directed by the algorithmic software, can automatically determine signal path profile parameters using algorithmically defined relationships associated with the discrete signal uplink data such that a signal communicated between the base unit and each antenna will be characterized by a signal delay distinct to each antenna.

55 (Previously presented). The time-division duplex (TDD) data communication system according to claim 54 further comprising at least one mobile terminal having a joint detector configured to demodulate a delayed TDD mode communication signal received from the base station.

56 (Original). The time-division duplex (TDD) data communication system according to claim 55 wherein the joint detector is a zero-forcing block linear equalizer.

57 (Original). The time-division duplex (TDD) data communication system according to claim 55 wherein the joint detector is a zero-forcing block linear equalizer having decision feedback capability.

Appl No. 09/523,329
Amendment dated November 23, 2004
Reply to Office action of August 24, 2004

58 (Original). The time-division duplex (TDD) data communication system according to claim 55 wherein the joint detector is a minimum-mean-square error equalizer.

59 (Original). The time-division duplex (TDD) data communication system according to claim 55 wherein the joint detector is a minimum-mean-square error equalizer having decision feedback capability.

60 (Canceled).

61 (Currently amended). The time-division duplex (TDD) data communication system according to claim ~~54~~ 60 wherein the algorithmic software is configured to further direct the data processor such that the data processor can determine new signal path profile parameters to re-characterize the signal delay distinct to each antenna when the discrete signal uplink data received by the base unit are sufficiently changed to require that a distinct signal delay change by at least one chip from an existing distinct signal delay.

62 (Original). The time-division duplex (TDD) data communication system according to claim 54 wherein the TDD signal is associated with a code division multiple access data signal.